

Virutex PEB250 Handheld Edgebander-



Virutex's PEB250 has been developed from their popular hand-held glue pot range of machines, and is perfect for edgebanding large tops or for use on site.

The PEB250 features variable speed adjustment. Controlled via a microprocessor on one of the hand grips, this means you can slow the feed rate down around curves, and speed up on the straights. Other features include variable temperature control and adjustable glue application.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2024 W & R Jack Limited.



Virutex PEB250 Handheld Edgebander-



Speed adjustment

With speed managed by microprocessor, you're in control.



Adjustable guide support

Combined with adjustable speed, the guide - with measurement in mm - gives you complete control over your edgebanding.



Easy cleaning of glue pot

Glue pot and tape sliding base covered by Teflon® for easy cleaning and maintenance.

Overview and features

Specifications

Feed speed	2, 4, 5, 6m/min
Working temperature	120 - 200°C
Panel thickness	10 - 62mm
Tape thickness	0.4 - 3mm
Total input power	830W (1.1hp)

Specifications are subject to change without notice.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2024 W & R Jack Limited.

