

Felder G380 Edgebander-

FELDER



The compact hot-melt Edgebanding solution for quality and performance.

Maximum performance in the smallest amount of space! Your Felder G380 occupies a total length of only 2.8 metres ensuring precious space is not unnecessarily wasted in your workshop.

The compact design of processing units ensures you still receive a fantastic result from this space saving edgebander. In addition to the compact size, the 8m/min feed speed ensures a high throughput of workpieces.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2025 W & R Jack Limited.



Felder G380 Edgebander-

FELDER



Pre-milling Unit

The two diamond tipped milling heads rotate in opposite directions preparing a perfectly straight and perpendicular workpiece edge to which the edge material is glued. The pre-milling unit also removes imperfections such as chips or tears in the melamine along the edge to improve the appearance and quality of the finished edge.

- Pre-milling depth 0 – 2mm



Operating Panel

A clear and easy to understand control panel is found on the G380. Each unit can be individually selected from the panel.

The G380 controller automatically engages a stand-by temperature if the machine is idle for 20 minutes. This maintains the integrity of the glue by keeping it at the application temperature for the shortest possible time, preventing 'cooking' the glue



Pressure Bar Adjustment

The large scale assists with setting the pressure bar height to match the workpiece thickness both accurately and quickly. • Workpiece thickness 10 – 45mm.

Overview and features

- Compact modern edgebanding technology in just 2.8 metres of workshop space
- Centralised control panel for a premium level of user comfort
- Heavy-duty chain feeder ensures optimal results from all units
- Pre-milling for the perfect preparation of the edge prior to tape application
- Teflon coated gluepot with 1.2kg glue capacity for larger runs
- Quick change glue-pot system allowing colour matching of glue to edge material
- Felder "Quick-Set" system for pre-set adjustments of processing units
- Combined end trim and profile trimming unit for either flush trim or rounding of corners

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2025 W & R Jack Limited.



Felder G380 Edgebander-

FELDER.

Specifications

Weight	450kg
Tape thickness	0.4 - 3mm
Panel thickness	10 - 45mm
Feed speed	8m/min
Minimum workpiece length	210mm
Minimum workpiece width	70mm

Specifications are subject to change without notice.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2025 W & R Jack Limited.

