



Give your workpiece a new face!

The solid machine chassis of the robust brushing machine structura offers maximum stability. With a working width of 650 mm and a variably adjustable infeed height of 3 to 200 mm, the machine is also suitable for larger workpiece requirements. The single sided mounting of the aggregates enables the processing of oversized workpieces.

The infeed with a table height of 900 mm and a continuous feeding belt with a web structure has an adjustable speed of 2.5-10 m/min.

**Auckland**

19 Allens Road, East Tamaki  
Auckland 2013  
Ph (09) 271 7700  
Fax (09) 271 7728


**Christchurch**

159 Ferry Road, Waltham  
Christchurch 8011  
Ph (03) 366 2013  
Fax (03) 366 2021

**Call free: 0800 522 577**

Copyright © 2025 W & R Jack Limited.





## Through feed height of 3-200 mm

With a working width of 650 mm and a variably adjustable infeed height of 3 - 200 mm, the machine is also suitable for larger workpiece requirements.



## Machine chassis open to one side for extra wide workpieces

The solid machine chassis and robustness the Structura offers maximum stability. The single sided mounting of the aggregates enables the processing of oversized workpieces.



## Control panel

The clearly structured and intuitive operating control panel offers maximum operating comfort for maximum productivity.

## Specifications

<b>Motor</b>	4 kW (5.5 hp)
<b>Weight</b>	850kg
<b>Dimensions (W x D x H)</b>	1455 x 1070 x 1250mm

Specifications are subject to change without notice.