

# Homag EDGETEQ S-240 series-

**HOMAG**



**Auckland**  
19 Allens Road, East Tamaki  
Auckland 2013  
Ph (09) 271 7700  
Fax (09) 271 7728

**Christchurch**  
159 Ferry Road, Waltham  
Christchurch 8011  
Ph (03) 366 2013  
Fax (03) 366 2021

**Call free: 0800 522 577**  
Copyright © 2025 W & R Jack Limited.



# Homag EDGETEQ S-240 series-



Homag is the worldwide market leader of edgebanders, and their EDGETEQ range is perfectly suited to the small to mid-sized companies of New Zealand. The EDGETEQ S-240 series provides complete solutions for the small to medium sized shop:

Compact and affordable, and based on the popular 'Ambition' range (previously branded 'Brandt'), Homag's EDGETEQ S-240 machines offer precision and quality at an affordable price.

Automating units for the first time provides you with perfect results and easy operation. Our short and compact models enable you to fully process your workpieces in the smallest possible space. These machines enable you to meet demands such as the trend for zero joints.

## Benefits

- 11 different models to meet every requirement
- Perfect edges
- Optimum entry-level machine
- Short and compact machines
- Intuitive operation - innovative easyTouch control system
- Robust design

For the most demanding standards of quality and reliability there is no substitute for a Homag.

### Auckland

19 Allens Road, East Tamaki  
Auckland 2013  
Ph (09) 271 7700  
Fax (09) 271 7728

### Christchurch

159 Ferry Road, Waltham  
Christchurch 8011  
Ph (03) 366 2013  
Fax (03) 366 2021

**Call free: 0800 522 577**

Copyright © 2025 W & R Jack Limited.



## Overview and features

(Please note specifications vary by model)

- For banding edge thicknesses up to 3 (6) mm and workpiece thicknesses up to 50 (60) mm
- Also available with joint trimming unit for a perfect cut and an optimum glue joint
- Excellent ease of use and operating safety thanks to the state-of-the-art touchscreen control system
- Profile trimming unit for rounding corners - complete processing
- Zero joints - airTec unit for a perfect zero joint finish
- Short setup times thanks to pneumatic adjustment of the units
- Multi-stage technology for highly flexible use with changing materials

## Specifications

<b>Feed speed</b>	11m/min
<b>Panel thickness</b>	8 - 50mm (opt to 60)
<b>Tape thickness</b>	0.3 - 3mm
<b>Solid strip thickness</b>	Optional to 6mm

Machines in the EDGETEQ S-240 range include:

Model 1210  
Model 1220 F  
Model 1210 HF  
Model 1220 AT  
Model 1220 C  
Model 1220 FC  
Model 1220 HF  
Model 1230 AT  
Model 1230 FC  
Model 1230 HF  
Model 1240 FC

Specifications are subject to change without notice.