KDT KE-268JSA Edgebander-





Packing the units of a much larger edgebander into a heavy-duty, space-saving 4230mm frame, the KE-268JSA delivers professional results without the premium price. The KE-268JSA offers unbeatable value with pre-milling, trimming, corner roudning and buffing. Weighing an impressive 1700kg, the KE-268JSA is no light-weight toy.



KDT KE-268JSA Edgebander-





Control Panel

KDT's large 10" intuitive touchscreen sets new standards in user convenience. You're in total control. Select and adjust processing units, height of the feed beam, position of the infeed fence and pressure zone. Trouble shooting diagnostics and service reminders also help keep your KE-268JSA running smoothly.



Infeed Fence

A polished chrome steel infeed fence and table provide ample support to feed workpieces easily and accurately.



Pre-Milling Unit with Diamond Tooling

For removal of imperfections in the panel edge and edge swelling immediately prior to gluing. Improves edgebanding quality, appearance and bond strength.

Overview and features

- Top Belt Pressure Beam Motorised Adjustment
- · Solid Polished Steel Infeed Fence
- Separating Agent Spray Unit
- Pre-Milling Unit with Diamond Tooling
- Infra-Red Panel Edge Heating Unit
- EVA Pre-Melt Unit
- Gravity Fed, Quick-Change EVA Hot-Melt Glue Application Unit
- Pressure Zone
- End Trimming Unit
- Fine Trim Trimming Unit with R1 Diamond Tooling and Hinge Hole Bridging
- Corner Rounding Unit with R1 tooling
- Radius Scraping Unit R1 with Hinge Hole Bridging
- Flat Glue-Joint Scraping Unit
- Detergent Spray Unit
- Buffing Unit



KDT KE-268JSA Edgebander-



Specifications

Weight 1700kg
Feed speed 8 - 12m/min
Tape thickness 0.4 - 3mm
Panel thickness 9 - 60mm

Dimensions (L x W x H) $4230 \times 860 \times 1690$

Specifications are subject to change without notice.

