



With models ranging from air volumes of 900m³/hr to 6,950 m³/hr, the Felder RL series are certified clean-air extractors with residual dust levels of less than 1mg/m³. With a large range of models, both small trade and larger industrial workshops can benefit.


A short and compact design makes these extractors perfect for workshops with low ceilings. The easily removable dust collection bins and low noise emissions help ensure operator comfort at all stages.

Features such as automatic filter cleaning, automatic extractor start, automatic fire extinguishers (powder or water) and connection to a briquetting press are available as an option on specific models.



Easily accessible waste disposal

Simply lift the lever to unlock the waste bin, roll the waste bin from underneath the unit and replace the collection bags as required. A viewing window allows you to monitor the bins to ensure they do not become overfilled.



Superb filtration with a large filter area

All RL models feature high quality filters which provide a dust emission quality of less than 0.1mg/m³ for a clean workshop and healthy operators. On the RL 250 model upwards, the filter plates are replaced with pleated filters (pictured) which provide a larger filter area in a similar amount of space.



Automatic filter cleaning

Available on specific models, the continuous pneumatic cleaning of the filters helps ensure high airflow and suction capabilities.

Specifications

Air flow To 6,950m³/hr

Dimensions (L x W x H) Varies according to your specification

Specifications are subject to change without notice.