

Felder F 348 Power Feeder-

FELDER.



Constant feed speed and exact guidance of your workpiece means standard tasks are performed precisely and safely.

Felder's F348 offers 3 driven rollers and four feed speeds to give you the control and accuracy you need, and the advanced tilting head allows for every conceivable position.

Advantages: Exact and clean work, constant feed speed, uniform and precise results. Advanced tilting head for every feed position.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2025 W & R Jack Limited.



Felder F 348 Power Feeder-

FELDER

Overview and features

Please note, power feed units fitted to a machine should stop when the machine stops.

It is advisable that this power feed unit is integrated to the primary machine's emergency stop circuit.

Specifications

Motor	.75kW (1hp) 3phase or .58kW (.78hp) 1phase
Drive system	3 rollers
Feed speed	8 spd (3.2/6.3/8.3/12.5/16.7/25/32/63 m/min)
Weight	59kg
Rollers	120mm Ø, 60mm wide

Specifications are subject to change without notice.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2025 W & R Jack Limited.

