



Through lateral movement of the saw blade and spindle, a quick change HSK 63 system and control panel layout, the UPT 150/1 provides maximum functionality, versatility and ease of use.

- Encased on all sides to minimise noise and keep the operator safe
- A very heavy duty cast iron frame helps ensure excellent performance and accuracy
- HSK 63 quick change spindle
- Three decimal position readouts with quick locking system
- Manual tenoning carriage with lineal bearings sliding on round bar

Saomad UPT 150/1-



Specifications

Maximum tenon length	150mm
Maximum cutting width	320mm
Maximum cutting height	125mm
Motor saw and tenon head	6.7kW (9.5hp)
Motor cope head	3kW (4hp)
Max. cope cutter size	320mm
Max. saw blade Ø	400mm
Bore Ø cope spindle	HSK63 x 40mm
Bore Ø saw spindle	30mm
Spindle speed cope spindle	3600 rpm
Spindle speed saw spindle	300 rpm
Sliding table area	1030 x 320mm
Weight	1700kg

Specifications are subject to change without notice.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2024 W & R Jack Limited.

