



The Peanut Mini Jig is a fast and simple solution for woodworkers who wish to take advantage of the Peanut System.

The Peanut Mini Jig's compact size and ease of use makes it perfect for projects of all sizes. Making joints with the Peanut Mini Jig can be learnt in minutes.

The Peanut Jig is compatible with the Peanut 2 and Peanut 2 Short connectors, as well as having the ability to create loose tenon and dowels joints (size up to 10mm). By repositioning the jig, Peanut joints can be created on any size panel. Depending on the application, we recommend that the Peanut slots are positioned approximately 200mm apart.

Key benefits:

- Fast and simple jointing solution for woodworkers
- Compatibility with 3 different invisible connecting systems
- Quick and simple positioning using the gravity studs
- Adjustable fence allowing you to make 45° and 90° angled joints
- Bespoke jig for use with handheld routers
- Small size and ease of use make it perfect for all types of projects

Tooling Requirements: Peanut® Cutter

IF Peanut Mini Jig Set-




Setup your jig

Clamp your jig to your work piece and align your work



Machining

Rout your Peanut Slot with the Peanut Cutter and drill your Peanut holes



Insert your Peanuts

The Peanut Jig is compatible with the Peanut 2 and Peanut 2 Short connectors

IF Peanut Mini Jig Set-



Overview and features

Adjustable fence enables the jig to be used for 90° joints on panels with thicknesses >15.3mm and 45° joints on panels with thicknesses >18mm.

Horizontal and vertical centre lines enable the jig to be used without the fence anywhere on a panel by aligning the centre lines with reference lines on the panel.

Countersunk screw holes along the horizontal centre line can be used to secure the jig when clamping is not possible, the screw holes will then be covered by the corresponding panel.

The Mini Jig features holes for gravity stopping studs for easy and quick positioning for edge joints. Notches in the jig body are a reference for central joints.

The shape of the jig body is ergonomically designed for easy gripping and also features a depth gauge to accurately set the Peanut cutter in the router.

The jig includes a 6mm drill bush and 6mm drill with stop which is used to drill a 6mm hole for the Peanut 2 or for 6mm dowels. Additional 5mm, 8mm and 10mm drill kits are available.

A standard 30mm router guide bush can be used with the Mini Jig (Note, a router guide bush is not included in the set). The guide bush projection should be no larger than 9mm to allow the router to sit flat on the jig body.