Ascent Machinery SM100T Spindle Moulder-





The Ascent SM100T spindle moulder offers affordable moulding technology for your workshop.

The 1-1/4" spindle accepts wide range of standard tools, and smooth running anodised aluminium table comes as standard. Four spindle speeds ensure the right rotation for your job while easy-to-set micro-adjustable fences keep your work precise.

If you've had enough of trying to get a professional result out of your hand-held router then the SM100T is the answer.

- Big table surface for easy and safe working
- 1-1/4" spindle accepts wide range of standard tools
- Smooth-running anodised aluminium sliding table
- Heavy-duty clamp for accurate, secure use of the sliding table
- Large, simple and safe controls, including spindle speed indicator lights.
- Work piece pressure rollers for secure positioning and burn free results.
- · Heavy cast iron table to absorb vibration
- Four spindle speeds for best finish & tool life
- Micro adjustable fences for quick & precise set up

Some assembly required.

Auckland 19 Allens Road, East Tamaki Auckland 2013 Ph (09) 271 7700 Fax (09) 271 7728 **Christchurch** 159 Ferry Road, Waltham Christchurch 8011 Ph (03) 366 2013 Fax (03) 366 2021





Ascent Machinery SM100T Spindle Moulder-





Simple control panel

Controls are conveniently located all together.



Easy to adjust

Easily adjusted anodised aluminium fence with clear measurement and firm clamping.



Fine control for excellent results

Workpiece pressure rollers for secure positioning and burn-free results. Fine threaded knobs for independent micro-positioning of both fence plates.

Specifications

Motor	2.2kw (3hp)
Spindle Ø	1 ¼"
Spindle speeds	1800, 3000, 6000 & 9000rpm
Table opening Ø	max.180mm
Spindle tilt	-10 to +30°
Sliding table stroke	800mm
Weight	210kg
Table size	700 x 640mm

Specifications are subject to change without notice.

Auckland 19 Allens Road, East Tamaki Auckland 2013 Ph (09) 271 7700 Fax (09) 271 7728 **Christchurch** 159 Ferry Road, Waltham Christchurch 8011 Ph (03) 366 2013 Fax (03) 366 2021

