

Hammer F3 Spindle Moulder-

Hammer.



Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2025 W & R Jack Limited.



Hammer F3 Spindle Moulder-

Hammer.

Hammer's F3 - the tilting spindle moulder with incredible performance and ease of use!

This 4 speed moulder features accurate and timesaving adjustment with the professional spindle moulder fence. The tilting spindle moulder with integrated slot and tenon table and first-rate engineering technology offers you a machine concept to satisfy the highest demands at the lowest possible price.

- Sensational value for money
- Solid cast iron tables and units
- Innovative machine technology
- High quality, unique detail solutions as part of the standard package
- Mobile as an option
- Minimal space requirement
- Quickest changeover times
- Remarkably user friendly
- Quality and precision from Austria
- CE + GS dust certified

Please note machine images may show optional equipment.

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2025 W & R Jack Limited.





High performance main spindle

The high performance main spindle guarantees excellent results at every angle regardless of the material. The ergonomically laid out operating elements and the smooth tool change convinces with every application, day after day. An important detail is standard with Hammer: the forward and reverse run of the spindle for your safety when moulding.



Spindle fence: simple handling, maximum safety and precision

The Hammer spindle fence is suitable for tools with a diameter up to 220 mm. Both of the anodised aluminium fences can be easily set to the spindle moulder tool diameter being used. The adjustment for the depth of cut when moulding can be made on the outfeed fence plate with a range of -5 mm und +25 mm. The extraction connection diameter for the chip extraction on the fence is 120 mm. As an option, safety bars can be fitted into the aluminium fence for a continuous surface support and offer even more safety when moulding.

Overview and features

Specifications

Motor	3kW (4hp) single phase. 3 phase avail
Spindle Ø	1 ¼"
Spindle speeds	3000, 6000, 8000 & 10,000rpm
Spindle travel	100mm
Weight	350kg
Table opening Ø	180mm
Table size	950 x 370mm

Specs shown are for the standard model we offer, but Felder offer a wide variety of options, so talk to us about customising a machine to suit you.

Specifications are subject to change without notice.