



Workpieces up to 4300 mm in length can be sanded effortlessly with the FS 722, thanks to the 2200 mm table length and the depth of the machine stand.

The aluminium rollers ensure the sanding belt runs true and the professional sanding shoe and edge sanding module are valuable standard equipment.

- Optimum dust extraction
- Simple connection to existing systems
- Slatted frame made from sturdy beechwood
- Large support surface with integrated extraction
- Offset working field for edge sanding work

Please note machine images may show optional equipment.

Felder FS722 Stroke Sander-

FELDER



Removable middle table section

The table of the Felder belt sander has a removable middle section. This allows the sanding of frames and drawers.



Rubber-soled sanding shoe

The 150 mm wide, rubber soled professional sanding shoe has an asymmetrically mounted, 4 point adjustable suspension.



Large throat depth

The machine chassis of the Felder belt sander has a large throat depth. You can easily sand workpieces up to 4300 mm in length.

Specifications

Table size	2200 x 800mm
Motor	3kW (4hp) 3-phase
Sanding belt size	150 x 5750mm
Speed	25m/min
Dust extraction	160mm
Rise & fall	300mm

Specs shown are for the standard model we offer, but Felder offer a variety of options, so talk to us about customising a machine to suit you.

Specifications are subject to change without notice.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2025 W & R Jack Limited.

