Felder FW950 Classic Widebelt Sander-





Classic surface finishing from Felder's Classic FW range, the FW950 makes it affordable to take that next step into professional woodworking.

With generous specifications including variable speed, heights from 3 - 170mm and the accuracy and reliaibility you'd expect from Felder, the FW Classic range offers value and performance.



Felder FW950 Classic Widebelt Sander-





Clear control panel with simple adjustment of the aggregates

Adjusting of the aggregates, the feed speed and sanding depth can be carried out quickly, simply and accurately all from the control panel. A particular highlight is the digital grain compensation which does not require the machine to be opened. Using a switch on the control panel the machine can be set to the correct sanding belt grain or set to sand using the sanding shoe.



Belt guidance system

The belt guidance system scans the workpiece using a modular spotlight and activates the electro-pneumatic belt guidance system, which moves the belt fowards and backwards.

The belt control system regulates the belt movement with electronically guided photo cells. Should the belt be at risk of coming loose, the belt control system stops the belt motor immediately.



Sanding pad

Sanding pad for fine finishing and veneer work. The unit can be also be used without engaging the sanding pad, in combination with the contact roller aggregate for general sanding work with a two-belt operation.

Overview and features

- Powerful combination aggregate with electro-pneumatic sanding shoe
- Electronic height adjustment with digital display
- Complete reliability in professional use
- Feeding belt control, hand safety stop and stop to ensure oversize pieces cannot be fed through
- First class manufacturing and finishing standards
- Vibration-free power transmission
- Powerful and efficient



Felder FW950 Classic Widebelt Sander-



Specifications

Working width 950mm
Working height 3 - 170mm
Sanding belt size 970 x 1700mm
Dust extraction 1 x 120mm
Motor 7.5kW (10hp)

Weight 800kg

Feed speed Variable from 2.5 - 10m/min

Specifications are subject to change without notice.

