



From Felder's Industrial line of bandsaws comes the FB940.

- Electronically balanced, solid cast iron wheels
- Upper and lower blade guides
- Saw blade tension indicator
- Cast iron table, tiltable up to 20 degrees
- Cast iron fence

Please note machine images may show optional equipment.

Felder FB940 Bandsaw-

FELDER



Rip fence

Precise adjustments can be made with the cast iron fence on both sides of the blade. When working with large workpieces it can be tilted away below the table.



Upper and lower table guides

Felder bandsaws are equipped with upper and lower table guides with fine adjustable side and rear rollers.



Tiltable table

The machined and polished cast iron table can be tilted from 0°– 20°

Overview and features

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2025 W & R Jack Limited.



Felder FB940 Bandsaw-

FELDER.

Specifications

Motor	7.5kW (10hp)
Table size	820 x 1300mm
Weight	700kg
Table tilt	0 to 20°
Dust extraction	140mm
Working height	1060mm
Maximum cutting height	560mm
Wheel Ø	940mm
Rip capacity	910mm

Specs shown are for the standard model we offer, but Felder offer a wide variety of options, so talk to us about customising a machine to suit you.

Specifications are subject to change without notice.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2025 W & R Jack Limited.

