



A stationary, compact panel saw for the discerning, cost-conscious woodworker.

- Minimal space requirement
- Powerful 1.9 kW motor, 1x 230 V for every workshop
- Saw aggregate tiltable from 0° to 45°
- Very easy saw blade change
- Preparation for grooving tool insert
- Precision machine-cast saw table
- T-slots for mitre fence on both sides of the saw blade
- Saw fence on round steel shaft continuously adjustable
- Rolling carriage with lifting bar, optional
- Mitre fence for mitre cuts, optional

K2M – ideal for those who work in tight spaces but still demand high quality and performance!



Saw aggregate

The Hammer saw aggregate impresses with smoothness, precision and extreme user friendliness. The large cutting height of 80 mm leaves nothing to be desired. Saw blades with up to 254 mm diameter can be lowered completely below the level of the saw table. The saw blade is simple to access and can be changed with ease.



Continuously variable tilt range between 0° and 45°

The continuously variable tilt range between 0° and 45° ensures precise mitre cuts. End stops at the 0° and 45° position ensure exact positioning of the settings. A large scale allows precise positioning and easy read-out of the corresponding values. Both the height adjustment and the angle adjustment can be done directly from the operator's side. The scope of delivery includes 1 handwheel.



Machine Table with T-slot and mitre fence

The Hammer K2M is a compact panel saw. What characterises this machine in particular is that it does not come with a sliding table. Therefore, its dimensions are very compact.

The machine is equipped with a T-slot on both sides of the saw blade for cutting to length and mitre cuts. The mitre fence 423-043 can be inserted into this T-slot.

Overview and features

Hammer product code: 500-07-201

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2026 W & R Jack Limited.



Specifications

Max. saw blade Ø	254mm
Max. cutting height @ 90°	80.5mm (with 254mm blade)
Saw blade speed	5000rpm
Rip capacity	610mm
Working height	mm
Blade tilt	0° - 45°
Dimensions (L x W x H)	875 x 600 x 1210mm
Dust extraction	100mm
Prepared for grooving tool insert	Dado 5-20mm wide x 180 dia
Weight	150kg
Motor	1.9kW

Specs shown are for the standard model we offer. Variants may be available.

Specifications are subject to change without notice.