

Felder K540S Panel Saw-

FELDER



If you are looking for precision, performance and quality at an affordable price then Felder's K540S is the machine for you!

- Felder 'X-Roll' sliding table as standard
- 137mm cutting height with a 400mm saw blade
- Stable and compact circular saw unit for long-lasting satisfaction
- 'Easy-Glide' tilting segment guide with a 6 year guarantee
- Zero point tilt for precise mitred cuts
- Maximum energy transfer from the Poly-V belt

Please note machine images may show optional equipment.

Auckland
19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch
159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577
Copyright © 2024 W & R Jack Limited.





'Easy-glide' system

A highly robust synthetic material located in the guidance track of the tilting brackets ensures they run smoothly, and are maintenance free even under the most extreme conditions. The tilt guide segment runs without lubrication and is insensitive to dust.



'X-Roll' sliding table

Felder's continuously developed linear guiding system has been astounding woodworkers since 1990. The high quality sliding table guiding technology, 'X-Roll,' offers amazing operating smoothness and is completely maintenance free. The 'x' design of the position of the roller bearings ensures that they move smoothly along hardened guides.



A simple and safe overhead guard

Highest operating safety and maximum flexibility when processing large-dimensioned workpieces: the new Felder overhead sawguard can be swung away easily and is always there where it is required.

Overview and features

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2024 W & R Jack Limited.



Specifications

Motor	5.5kW (7.5hp) 3 phase
Weight	680kg
Max. saw blade Ø	400mm
Max. cutting height @ 90°	137mm
Saw blade speed	4000rpm
Rip capacity	1250mm
Working height	890mm
Sliding table length	2800mm
Crosscut fence length	2600mm
Outrigger table size	1300mm

Specs shown are for the standard model we offer, but Felder offer a wide variety of options, so talk to us about customising a machine to suit you.

Specifications are subject to change without notice.