

Felder K700 Professional Panel Saw-

FELDER



The operating safety and comfort of the new Felder K700 Professional is simply top class.

The innovative saw aggregate with precision guiding system for exact angle adjustments, zero point tilt and precise lineal height adjustment is just one of the numerous Felder innovations guaranteeing perfect woodworking results. The outrigger table guarantees efficiency and precision even when processing heavy or bulky workpieces. The new (optional) swing-away overhead saw guard offers maximum flexibility and maximum operating safety.

Please note machine images may show optional equipment.

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2025 W & R Jack Limited.



Felder K700 Professional Panel Saw-

FELDER



'Easy-Glide' system

A highly robust synthetic material located in the guidance track of the tilting brackets ensures they run smoothly, and are maintenance free even under the most extreme conditions. The tilt guide segment runs without lubrication and is insensitive to dust.



Scoring unit

For chip free cutting of laminated panels. The saw blade can be mechanically or electrically driven and can be set in both height and lateral position.



'X-Roll' sliding table

The continuously developed linear guiding system from Felder has been astounding woodworkers since 1990. The high quality sliding table guiding technology, 'X-Roll,' offers amazing operating smoothness and is completely maintenance free. The 'x' design of the position of the roller bearings ensures that they move smoothly along hardened guides.

Overview and features

Auckland

19 Allens Road, East Tamaki
Auckland 2013
Ph (09) 271 7700
Fax (09) 271 7728

Christchurch

159 Ferry Road, Waltham
Christchurch 8011
Ph (03) 366 2013
Fax (03) 366 2021

Call free: 0800 522 577

Copyright © 2025 W & R Jack Limited.



Specifications

Motor	5.5kW (7.5hp) 3 phase
Weight	560kg
Max. saw blade Ø	315mm
Max. cutting height @ 90°	104mm
Saw blade speed	4800rpm
Rip capacity	1250mm
Working height	890mm
Sliding table length	2050mm
Crosscut fence length	2600mm
Outrigger table size	1500mm

Specs shown are for the standard model we offer, but Felder offer a wide variety of options, so talk to us about customising a machine to suit you.

Specifications are subject to change without notice.