Fimal Concept 350 Saw-





A revolution in cutting, Fimal's Concept 350 offers the advantages of a beamsaw in combination with the versatility of a panel saw.

- Space savings the Concept 350 is available in 3 cutting lengths (2600 / 3200 / 3800mm) and on average requires 50% less space compared to similar capacity panel saws
- High productivity ability to cut two sheets at once and at a faster cutting speed compared to manual cutting
- Maximum safety a completely enclosed cutting area within the pressure beam provides unbeatable operator safety
- Excellent dust extraction the enclosed cutting area allows nearly 100% effective extraction results (depending on material height)
- Impressive quality of cut the electronically controlled blade-feed speed and pressure beam leads to superb results

Please note machine images may show optional equipment.



Fimal Concept 350 Saw-





Mobile control panel

The mobile control panel is easily movable to every work area on both the front and rear of the machine. There's electronic control of blade height, blade angle, ripping stop position and blade feed speed along with selection of cutting, grooving and scoring functions. When selected as an option, the panel is upgraded to an 8" touch screen which also allows the importing of cutting lists via USB with a visual cutting display.



Multi-stop rear table fence

The optional multi-stop fence which is mounted on a trolley comprises of four electronic stops (compared to the standard two) with a fence height of 26mm.



LED status lights

As an option, white, red and blue LED lights under the pressure beam signal the current operating status of the machine.

Overview and features

Specifications

 Motor
 5.5kW (7.5hp)

 Weight
 1210/1360/1510kg

Max. saw blade Ø 350mm
Max. cutting height @ 90º 100mm
Saw blade speed 4000rpm
Rip capacity 1300mm

Horizontal cutting length 2600/3200/3800mm

Crosscut fence length 2500mm
Rise & fall Motorised
Blade tilt Motorised

Specifications are subject to change without notice.

